

# DATA SHEET FOR METALLIZED POLYPROPYLENE CAPACITORS. OIL FILLED.

## WORKING VOLTAGE 250 V

Construction in aluminum tube with tinned copper wire.  
 Furnished with black shrinking sleeve and golden print.  
 RoHS compliant.  
 REACH compliant.

CAP.( $\mu$ F) Tol. -10%/ +10%	DIM. $\varnothing$ diam. x length (mm)	Max. ESR @100kHz/ 20°C (m $\Omega$ )
1,0	25 x 55	1600
2,2	25 x 55	800
3,3	25 x 55	630
4,7	25 x 55	400
6,8	25 x 55	300
8,2	30 x 52	220
10	30 x 52	200
15	40 x 55	150
22	40 x 55	100
25	40 x 55	70
33	45 x 55	40
47	50 x 55	22
50	50 x 55	18
100	50 x 100	10



OUR METALLIZED POLYPROPYLENE CAPACITORS, WHICH ARE OIL FILLED UNDER HIGH VACUUM, ARE A SUPERIOR ALTERNATIVE AS RESERVOIR CAPACITOR IN POWER SUPPLIES OR AS CROSSOVER CAPACITOR IN LOUDSPEAKER FILTERS.

LOW LOSS AND SUPERIOR DAMPING DUE TO THE OIL-FILLING PROVIDES YOU WITH A HIGH-QUALITY CAPACITOR IN HIGH-END AUDIO EQUIPMENT.

TEMPERATURE RANGE:	-25°C...+85°C
INSULATION:	Shrinking sleeve voltage proof > 2500 VAC
CLIMATIC CATEGORY IEC 60068:	25/085/56
LONG LIFE:	10000 h at 85°C
